

PARTNER

CARE . TRUST . RESPONSIBILITY

CD-7220 Customer Display



The CD-7220 is a top quality customer display in telescope style. The vacuum fluorescence display ensures pin-sharp character definition. The display retains its optimum legibility even in brightly lit environments.

The display can also optionally draw power from a printer, making it independent of a separate power supply unit.

The CD-7220 is adjustable in height and can be matched to the requirements of any working environment.

Special Features:

- Vacuum fluorescence display
- 270° rotation option
- Interface RS232 or USB
- Adjustable height
- Two-line display with 20 characters per line

Optional:

- External power supply 12V

Customer Display CD-7220

Technical data

Item	CD-7220
Display Method	Vacuum fluorescent
Display Color	Blue green
Brightness	700 cd/m ²
Interface	RS-232 Serial (D-Sub 9 pin) with pass through function, USB with 5V power (do not require power supply)
Power Supply	12V
Power Consumption	5 Watt / 8 Watt
MTBF	25.000 hours
Viewable Angle	+/- 15 ° C
Rotation Angle	Max 270 ° C
Character Font	5 x 7 dot matrix, comma and decimal point
Character Size	9.0 mm x 5.25 mm
Character Type	96 alphanumeric, 13 sets and one variable
Number of Characters	40 (20 columns x 2 rows) 40 (20 columns x 2 rows) x 2 sides
Dimension	109 mm Base or 42 mm VFD (L) x 230 mm (W) max. 504 mm (H) with long & short pole
Options	Dual Side Display



atecresa
Software de Gestión y TPV desde 1982
922 824 810 - 928 987 101 - info@atecresa.com

