

Audrey A5 TOUCH POS SYSTEM



The Audrey A5 is a reflection of Partner Tech's future vision of the POS with complementary stylish features and innovation design. A technology rich solution that offers industrial grade performance with a high-quality design will make a dramatic statement in your store's environment.

The Audrey A5 with small form factor design that's fully functional as a point-of-sale, kiosk or self-service unit. Can be adjusted in positions from 90 degrees to lay-flat design based on business requirements

The Audrey A5 transcends all verticals with Intel processors ranging from SKYLAKE and KABYLAKE platforms, advanced RAM and SSD options gear towards optimizing performance in a feature rich solution. This, coupled with the slim and sleek look, distinguishes itself from the traditional POS solutions offered in the market today.

SPECIAL FEATURES

- 15.6" wide screen all-in-one POS with FHD resolution and PCT
- Latest SKYLAKE / KABYLAKE high performance Intel CPU with fanless design
- Front panel IP65, whole device IP54 certified
- Maintenance and service friendly design
- High speed M.2 PCIe SSD
- Supports up to 3 independent displays (operation, customer facing display and digital signage)
- Slim and stylish design for retail and hospitality

OPTIONAL

- MSR, IC card reader, Fingerprint, RFID, i-Button, VFD, Camera
- 7", 11.6", 15.6" second displays

A5



Item	A5
Display	15.6", Resolution 1366 x 768 / 15.6" Resolution 1920 x 1080 (Optional)
Touch	15.6" Pcap Touch
CPU	Intel® Core™ i5-6300U Processor (SKYLAKE-U Co-lay)
	Intel® Core™ i3-6100U Processor (SKYLAKE-U Co-lay)
	Intel Celeron Processor 3955U (SKYLAKE-U Co-lay)
	Intel Celeron 3965U (KABYLAKE-U Co-lay)
	Intel® Core™ i3-7100U (KABYLAKE-U Co-lay)
	Intel® Core™ i5-7300U (KABYLAKE-U Co-lay)
Memory	2 x 260 pin DDR4 SO-DIMM-2133 vertical type, Standard Spec: 4GB, 8GB, 16GB
Storage	M.2 PCIe SSD, 128G / 256G
External I/O Interface	2 x Serial ports, RS232 (RJ45), OV/5V/12V selection by BIOS (COM1, COM2)
	2 x LAN, (IEEE 802.3 10/100/1000 Mbps Ethernet, RJ45)
	1 x RJ11 port supports 2 cash drawers with 24V / 12V by jumper setting
	1 x DC+12V out
	4 x USB Type-A ports (USB3.0/2.0)
	1 x DC +12V input power-jack
	1 x Audio (1 * Line-out)
	1 x HDMI port
	1 x VGA
Optional Powered USB	4 x Powered USB (3x12V + 1x24V, on the stand or on PS-103)
Speaker	1 * Speaker 3W
Optional Peripheral	MSR, IC Card Reader, Fingerprint, RFID, i-Button, VFD, Camera
Display Support	3 Independent Displays (Main Display + VGA + HDMI)
Expansion	Mini-PCle interface
Intel V-Pro	YES (i5 CPU only)
OS Support	POSReady7 (32-bit / 64-bit, SKYLAKE-U only)
	Windows10 Enterprise IoT LTSB 64-bit
Adapter	Linux Ubuntu 16.04 / 18.04 64-bit
Adaptor	AC-In 100~240V / DC-Out 12V, 90W / 180W
Mechanical	1. Front Panel IP65, whole system IP54, Fan-less Operation 2. VESA 75 x 75
Dimensions	2. VESA 75 x 75 W15.43 x H12.6 x D7.87 inch
	W15.43 X H12.6 X D7.87 INCh 12.13 lbs
Weight	12.13 IDS

*Specification is subject to change without prior notice







PARTNER TECH USA INC.

15320 Barranca Parkway Suite 150. Irvine, CA 92618 TEL: +1-949-598-1888 sales@partnertechcorp.com